



Commercial Downlights

Features

- Available in 4", 6", 8" and 10" models
- Available in 100-277V AC and 100-347VAC input options
- 0-10V dimming
- Damp rated
- 40° beam angle
- Really commercial retrofit solution



Dimensions

Size	Height	Diameter
4inch	7.17"	5.59"
6inch	8.64"	7.48"
8inch	8.98"	9.29"
8inch (S4W)	9.76"	9.29"
10inch	9.25"	10.98"
10inch(S4W)	10.00"	10.98"



Certificate



Specification

Model	Size Options	Input Power	Luminous Flux	Efficacy	CRI	Input Voltage
NLC4-D27W-XXX	4" [COB]	27 Watts	1886 lm	70 lm/w	Ra>80	100-277V AC
NLCES-18W-XXX	6" 8"	18 Watts	1600 lm	89 lm/w	Ra>80	100-277V AC / 100-347V AC
NLCES-27W-XXX	6" 8" 10"	27 Watts	2300 lm	88 lm/w	Ra>80	100-277V AC / 100-347V AC
NLCES-40W-XXX	6" 8" 10"	40 Watts	3350 lm	83 lm/w	Ra>80	100-277V AC / 100-347V AC
NLCS-D54W-XXX	8" 10"	54 Watts	4500 lm	87 lm/w	Ra>80	100-277V AC / 100-347V AC