



Recessed Flat Panels

Features

- ETL / UL And DLC
- Achieving 125 lm/w (DLC4.2 Premium)
- 100-277V or 120-347V AC input options
- 0-10V dimming
- 5 years limited warranty
- Damp rated



Dimensions

Size	L	W	H
1'x4'	11.70"	47.70"	1.09"
2'x2'	23.70"	23.70"	1.09"
2'x4'	23.70"	47.70"	1.09"



Certificate



Specification

Model	Input Power	Luminous Flux	Efficacy	Input Voltage	CRI	Dimming type	Certificate
NLVS22-DM**	40 Watts	4400lm / 5000lm	110 LPW / 125LPW	100-277V AC	Ra>80	0-10V Dimming	UL/ETL, DLC
NLVS24-DM**	50 Watts	5600lm / 6200lm	110 LPW / 125LPW	100-277V AC	Ra>80	0-10V Dimming	UL/ETL, DLC
NLVS14-DM**	40 Watts	4000lm	100LPW	100-277V AC	Ra>80	0-10V Dimming	UL/ETL, DLC
NLVP22-DM-XXX	40 Watts	4400lm / 5000lm	110 LPW / 125LPW	120-347V AC	Ra>80	0-10V Dimming	UL, DLC
NLVP24-DM-XXX	50 Watts	5500lm / 6250lm	110 LPW / 125LPW	120-347V AC	Ra>80	0-10V Dimming	UL, DLC
NLVP14-DM-XXX	40 Watts	4000lm	100LPW	120-347V AC	Ra>80	0-10V Dimming	UL, DLC

Remark: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/tsp.