

# AIR FLAT

SURFACE MOUNTED PANEL



## Features

- Thinnest surface mounted panels
- ETL/UL and DLC
- Step dimming and 0-10v dimming function combination
- High efficacy, up to 125lm/w (DLC4.2 Premium)
- Damp rated
- 5 years limited warranty

## Dimensions



Size	L	W
1'x1'	11.85"	11.85"
1'x2'	11.85"	23.70"
1'x4'	11.70"	47.70"
2'x2'	23.70"	23.70"
2'x4'	23.70"	47.70"

## Certificate



## Specification

Model	Size	Input Power	Luminous Flux	Efficacy	Input Voltage	Dimming type	Certificate
NLFS11-18W-XXX	1'x1'	18 Watts	1700 lm	95 lm/w	100-277V AC	0-10V Dimming	UL
NLFS21-25W-XXX	1'x2'	25 Watts	2500 lm	100 lm/w	100-277V AC	0-10V Dimming	UL
NLFS22-DL-XXX	2'x2'	27 Watts	2970 lm	110 lm/w	100-277V AC	0-10V Dimming	ETL, DLC
NLFS24-DM-XXX	2'x4'	40 Watts	4400 lm	110 lm/w	100-277V AC	0-10V Dimming	ETL, DLC
NLFS14-DM-XXX	1'x4'	40 Watts	4000 lm	100 lm/w	100-277V AC	0-10V Dimming	ETL, DLC
NLFS22-DM-XXX	2'x2'	40 Watts	4400 lm/5000 lm	110 LPW/125 LPW	100-277V AC	0-10V Dimming	ETL, DLC
NLFS24-DH-XXX	2'x4'	50 Watts	5500 lm/6200 lm	110 LPW/125 LPW	100-277V AC	0-10V Dimming	ETL, DLC

Remark: Not all products are qualified on the DLC GPL. To view our DLC qualified products, please consult the DLC Qualified Products List at [www.designlights.org/gpl](http://www.designlights.org/gpl).