

EMERGENCY LED DRIVER

Emergency Solution For LED Luminaires



T-Grid Box Hanger Accessory Available

Emergency LED Driver

Features

- UL component recognized
- 90 minutes operation for battery backup
- Applicable to most LED luminaires
- Adopt long life recyclable Ni-cad battery
- Including test switch and charge indicator accessory kits
- 5 years limited warranty

Dimensions



Models	A	B	C
8W	2.18"	2.17"	10.42"
12W	2.18"	2.17"	10.42"
18W	2.72"	2.80"	14.84"
25W	2.72"	2.80"	14.84"

Applicable To LED Luminaires With External Driver

Model	Output Power	Input Current	Emergency Time	Output Voltage	Recharge	Input Voltage
NLEL-0848-XXX	8 Watts	65mA (max)	>90 Minutes	12-48V DC	24Hrs	100-277V AC / 120-250V AC
NLEL-1248-XXX	12 Watts	65mA (max)	>90 Minutes	12-48V DC	24Hrs	100-277V AC / 120-250V AC
NLEL-2548-XXX	25 Watts	80mA (max)	>90 Minutes	18-48V DC	48Hrs	100-277V AC / 120-250V AC

Applicable To LED Luminaires With Internal Driver

Model	Output Power	Input Power	Emergency Time	Output Voltage	Recharge	Input Voltage
NLEH-18170-XXX	18 Watts	6 Watts	>90 Minutes	170V DC	40Hrs	100-277V AC / 120-250V AC
NLEH-25170-XXX	25 Watts	6 Watts	>90 Minutes	170V DC	48Hrs	100-277V AC / 120-250V AC